



US008118578B2

(12) **United States Patent**
McIntyre

(10) **Patent No.:** **US 8,118,578 B2**
(45) **Date of Patent:** **Feb. 21, 2012**

(54) **ROTARY PUMP WITH SLIDING CRESCENTOID ROTOR BODIES**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(76) Inventor: **John McIntyre**, Traverse City, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 713 days.

(21) Appl. No.: **12/334,054**

(22) Filed: **Dec. 12, 2008**

(65) **Prior Publication Data**

US 2010/0150763 A1 Jun. 17, 2010

(51) **Int. Cl.**

F01C 19/00 (2006.01)

F04C 2/00 (2006.01)

(52) **U.S. Cl.** **418/142; 418/54**

(58) **Field of Classification Search** **418/142, 418/54**

See application file for complete search history.

984,904	A *	2/1911	Greene	418/54
2,205,705	A *	6/1940	Whitehurst	418/142
4,030,861	A *	6/1977	Putz	418/54
4,300,874	A *	11/1981	Georgiev	418/54
4,507,067	A	3/1985	Hansen	
4,519,206	A	5/1985	van Michaels	
4,938,671	A	7/1990	Thompson	
5,032,069	A	7/1991	Parsons	
5,472,327	A	12/1995	Strikis et al.	
2006/0233653	A1	10/2006	Trapalis	

* cited by examiner

Primary Examiner — Mary A Davis

(57) **ABSTRACT**

A rotary pump device includes a stator chamber with a cylindrical inner wall having intake and exhaust ports therein, and a two-part, expanding rotor eccentrically mounted for rotation within the chamber. The rotor comprises two crescentoid bodies with end surfaces in sliding, mating contact. A spring rod is placed between the inner rotor body surfaces to maintain rotor contact points in continuous wiping contact with the chamber wall. A full intake/exhaust cycle occurs every 180° of rotor travel.

11 Claims, 3 Drawing Sheets

